




型号 Model		ZJ5820	ZJ5821	ZJ5822	
面线 Upper thread	面线剪线装置 Upper thread trimmer	长线剪切 Long thread cut	长线剪切 Long thread cut	短线剪切 Short thread cut	
剪线装置 Thread trimmer	底线剪线装置 Lower thread trimmer	无 No	长线剪切 Long thread cut	短线剪切 Short thread cut	
用途 Filed of application	女装、男装，休闲装，牛仔裤，裤装 Ladie's wear Men's wear, casual wear, jeans, trousers	男装，休闲装、女装，牛仔裤，裤装 Ladie's wear Men's wear, casual wear, jeans, trousers	男装，休闲装、女装，牛仔裤，裤装 Ladie's wear Men's wear, casual wear, jeans, trousers	牛仔裤，裤装 Jeans, Trousers	
功能 Features	剪线装置仅剪切面线。 可缝纫最长为50mm的扣眼。 Only the upper thread is cut by the thread trimmer. Buttonholes up to 50mm long can be sewn.	剪线装置将较长地剪切所有线头。在缝纫持续过程中可在更长距离内安全把握线尾。很合适要求精确剪切线头或手动剪线的情况。 All the threads are cut into long end by the thread trimmers, and the thread end will be safely held in longer distance when sewing, it is suitable for cases that require accurate thread end or manual trimming.	剪线装置将较短地剪切线头，这样可省去手动剪线的麻烦和降低耗线量。 All the threads are cut into short end by the thread trimmers. This saves the manual trimming and reduces consumption of the thread.		
缝纫形状 Sewing shape					
缝纫长度 Sewing length	圆头锁眼 Eyelet buttonhole : 8-50mm 直形钮孔 Straight buttonhole : 5-50mm	圆头锁眼 Eyelet buttonhole : 8-42mm 直形钮孔 Straight buttonhole : 5-42mm	22-30 mm	18-26 mm	
压脚长度(标准) Length of work clamp(standard)	30mm		30 mm	26 mm	
刀垫的长度(标准) Length of hammer(standard)	22mm		24 mm	20 mm	
刀垫的长度(附件) Length of hammer(accessory)	30mm		28 mm	24 mm	
缝纫速度 Sewing speed	1,000-2,500rpm				
针码 Stitch pitch	0.5-2.0mm				
之字缝宽度 Zigzag width	1.5 - 5.0 mm (在机械条件下最宽为4.0 mm之字缝宽度补偿最多为5.0) (Up to 4.0mm in mechanical, up to 5.0mm with zigzag width compensation)				
之字缝宽度(出厂设置) Zigzag width(factory setting)	2.5mm		3mm		
流线加固缝长度 Taper bartack length	0-20mm				
压脚高度 Height of work clamp	标准高度为12 mm (最高可达16 mm) 12mm as standard (Available up to 16mm)		16mm		
送布装置 Feed mechanism	3个脉冲马达的间歇送布 (X, Y, θ) Intermittent feed by 3 pulse motors (X Y θ)				
机针 Needle	DOx558 Nm100 (蓝狮/SCHMETZ)	DOx558 Nm90 (蓝狮/SCHMETZ)	DOx558 Nm110 (蓝狮/SCHMETZ)		
安全设备 Safety equipment	若有问题发生，有紧急停止功能和由安全电路驱动的内置自动停止设备 Emergency stop function and built-in automatic stopping device activated by safety circuit in case of trouble				
上轴马达 Upper shaft motor	AC 伺服马达550W AC servo motor 550W				
空气压力 Air pressure	主调整器 : 0.5 Mpa, 锤压调整器 : 0.4 MPa Main regulator : 0.5 Mpa, Hammer pressure regulator : 0.4 MPa				

## ZJ5780S series

### 高速直驱电子平头锁眼机系列

#### HIGH SPEED COMPUTERIZED LOCKSTITCH BUTTONHOLING MACHINE

新型切刀装置，布料剪裁更为精准；

采用五个高精度的进步马达，实现自动化操作；

多功能大型液晶色彩触摸操作面板，更直观调用各种放存花样；

具有连续缝、循环缝组合缝制，实现高品质与高效率完美结合。

Newly fabric cutter system makes the fabric cutting much accurately.

Adopts 5 step motors in the machine, to realize automatic operation.

Equipped with the continuous sewing and cycle sewing functions, highly improve the production efficiency.

ZJ5780S ZJ5780K ZJ5780L

**GREEN POWER**  
服装模板作业  
理想缝纫

